

### Cabinet Heater Series B



#### Special Features

- Thermal separation of the PTC heater from the external profile (patented)
- Limited external profile temperature
- Optimal convection

#### Technical data:

Model		90		120		150		200	
Nominal power output	at 10°C, 12V or 230V*	45W	60W	80W	100W	125W	150W	200W	230W
Rasted fan current (amps)	at 12V	0.06	0.06	0.06	0.06	0.06	0.06	0.06	0.165
Recommended fuse (time delay, amps)	at 12V/24V at 115V / 230V	6 2	6 2	n/a 2	n/a 4	n/a 4	n/a 4	n/a 4	n/a 4
Fan volumetict flow at zero static pressure	(m <sup>3</sup> /h)	12,4	12,4	12,4	12,4	12,4	12,4	12,4	17
Fan lifetime	at 40°C, L 10 hours	120.000	120.000	120.000	120.000	120.000	120.000	120.000	-
Input voltage (V)	fan DC	12/24	12/24	12/24	12/24	12/24	12/24	12/24	12/24
	heater	12/24	12/24						
Dimensions (mm)		100/240	100/240	100/240	100/240	100/240	100/240	100/240	100/240
	Cross section	42 x 42	42 x 42	42 x 42	42 x 42	42 x 42	42 x 42	42 x 42	42 x 42
	Length of profile and fan	72	72	72	72	107	107	107	107
Weight (kg)		0.175	0.175	0.175	0.175	0.260	0.260	0.260	0.275
Protection type		IP20	IP20	IP20	IP20	IP20	IP20	IP20	IP20
Cable length (mm)		600	600	600	600	600	600	600	600
Outlet finger guard	(High voltage supply)	y	y	y	y	y	y	y	y
Outlet finger guard	(Low voltage supply)	option	option	option	option	option	option	option	option